



AquaSorb® 1000

granular coal based activated carbon

AquaSorb® 1000 is a highly economical, medium activity granular activated carbon manufactured by steam activation from select grades of bituminous coal. The perfect balance between adsorption and transport pores provides optimum performance in a wide range of water treatment applications. The product is a high density adsorbent and provides maximum volume activity. The high hardness and mechanical strength ensures negligible losses during backwashing, air scouring and multiple reactivations.



Soft drink manufacturers and breweries rely upon AquaSorb® activated carbon for dechlorination and dissolved organic removal.

Specification*

lodine number	min. 850 mg/g
Moisture content	max. 5%
Total ash content	max. 15%
Wettability	min. 95%
Hardness	min. 95%

Typical Properties*

Surface area	900 m²/g
Methylene blue number	200 mg/g
Total pore volume	0.88 cm³/g
Water soluble ash	0.2%
Apparent density	510 kg/m ³
pH	8-11

Features and Benefits

- · Medium activity
- · Proven drinking water adsorbent
- · High density
- · High wettability
- · High hardness and abrasion resistance
- · Proven superior for multiple reactivations
- · Excellent adsorption capacity
- · Both adsorption and transport pores

Typical Applications

- · Treatment of municipal drinking water
- · Production of soft drinks and beer
- · Dechlorination of process water
- · Purification of MEA/DEA

Available Particle Sizes

- 20x50 mesh (0.30 0.85 mm)
- 12x40 mesh [0.425 1.70 mm]
- 8x30 mesh (0.60 2.36 mm)
- 8x20 mesh (0.85 2.36 mm)
- 8x16 mesh [1.18 2.36 mm]

Certifications and Approvals

- NSF / ANSI standard 61
- AWWA B604-96
- EN12915
- Kosher certified

Standard Packaging

- 25 kg bag (55 lb)
- 500 kg bulk bag (1100 lb)

